MariGreen

Update for the project

„Plug and Play Energypack for inland and shortsea shipping“

Prof. Dr. David Smeulders (TUE)

Jörn Josef Boll (M.A.) (MAH)

INTERREG Deutschland Nederland

Europäische Union
Europese Unie

www.marigreen.eu

MariGreen
Maritime Innovations in Green Technologies

Technische Universiteit
Eindhoven
University of Technology

Where innovation starts

TU/e:	11,000	BSc and MSc	Mech. Engng.:	1,500	BSc and MSc
	1,500	PhD		175	PhD
	2,000	faculty staff		100	faculty staff

INTERREG Deutschland Nederland

Europäische Union
Europese Unie

MariGreen
Maritime Innovations in Green Technologies

Maritieme Academie Harlingen

INTERREG Deutschland Nederland

Europäische Union
Europese Unie

MariGreen
Maritime Innovations in Green Technologies

Why hydrogen?

Overview storage capacity of different energy storage systems



Renewables Global Futures Report Great debates towards 100 % renewable energy

REN21 Renewable Energy Policy Network for the 21st Century

Source: Fraunhofer Institute, Germany, 2014

Hydrogen configuration





INTERREG Deutschland Nederland
Europäische Union Europese Unie
TU Delft
MariGreen
Maritime Innovations in Green Technologies

Fuel cells characteristics

	LT-PEMFC	HT-PEMFC	SOFC
Operating temperature (˚C)	40 - 80	150 - 180	500-1000
Electrical efficiency (LHV)	50-60	40-45	50-65
Fuel purity required	99.999% H2	CO<3%	Light hydrocarbons (S<20 ppm)
Gravimetric power density (W/kg)	250-1000	-	8.0-80
Volumetric power density (W/l)	300-1550	-	4.0-32
Life time	5 to 20k hours	10 to 60k hours	10 to 40k hours
Start-up time	<10 seconds	10 to 60 minutes	30 minutes to hours
Load transients (0 to 100%)	<5 seconds	2-5 minutes	<15 minutes
Capital cost today ($/kW)	>1000	4000-4500	3500-15000
Technology Readiness Level (TRL)	8	7-8	5-7
Cooling	Water cooling	Water cooling	Air cooling
Waste heat recovery	-	-/+	++

van Biert, L., Godjevac, M., Visser, K., & Aravind, P. V. (2016). A review of fuel cell systems for maritime applications. *Journal of Power Sources*, *327*(X), 345–364. https://doi.org/10.1016/j.jpowsour.2016.07.007

LNG Market Uptake (Starting Point)

Innovation Projects

- Low pressure LNG tank
- Plug and Play Energypack
- Standard modular LNG system
- Methane catalyst for LNG engines
- Training technologies







Goals

- Cost reduction for „small scale" LNG-propulsion
- Improvement of emissions of LNG-propulsion
- Safe operation of LNG-propulsion through training

INTERREG Deutschland Nederland

Europäische Union
Europese Unie

MariGreen
Maritime Innovations in Green Technologies

This is where we are now!

EMELI

Toekomstige situatie

"Kempenaar"
55m x 7.2m 682T 1961



Maritieme Academie Harlingen

INTERREG Deutschland Nederland

Europäische Union
Europese Unie

MariGreen
Maritime Innovations in Green Technologies

Steps to completion

- Project went to some major changes (LNG to Hydrogen)
- We are currently finalizing the technical planning
- Construction phase will commence in October 2018
- MV Emeli will serve as a test bed for the new propulsion installation and will gather data after the completion of the refit in “every day service” as a training vessel

INTERREG Deutschland Nederland

Europäische Union
Europese Unie

MariGreen
Maritime Innovations in Green Technologies

Hartelijk dank!
Dankeschön!
Thank you very much!

INTERREG Deutschland Nederland

Europäische Union
Europese Unie

MariGreen
Maritime Innovations in Green Technologies